

F7 Fingerprint Access Control

- Support 50 time zones
- Display up to 80 characters on LCD
- Built-in Relay
- Ethernet, RS232 and RS485 interface



Features:

- Audible indicators allows for real time operation
- Optical-base technology
- Support 50 time zones, 5 grouping, 10 groups
- LCD with 80 characters and blue backlit keypad
- Dismantlement alarm, break-in alarm
- Built-in relay
- Use of stand-alone mode or working in conjunction with Ethernet, RS232 and RS485
- Multi-language optional: English, Simplified Chinese, Traditional Chinese, Spain, Portuguese, Turkish, French, German, Arabia, Frasi, Japanese, Indonesian, Malay, and Thai, etc
- With check in/out function
- Centralized enrollment and real time monitor

Specifications:

- Verification Method: Fingerprint, ID+Password, Fingerprint/ (ID+Password)
- Verification Mode: 1:1 (500 / 1500 templates), 1:N (Less than 500 / 1500 templates)
- Verification Time: Less than 2.0 sec
- False Rejection Rate (FRR): Less than 1%
- False Acception Rate (FAR): Less than 0.0001%
- Capacity: 500 templates / 1500 templates
- Power Supply: DC12V (stay current: 50mA) (work cuurent: 400mA)
- Relay output: DC12V, 3A
- Communication: RS232, RS485, TCP/IP Weigand 26bits output
- Communication Speed: 115200 / 38400 / 19200 / 9600 BPS TCP/IP: 10MB/AUTO
- Log Data: 30000 / 100000 events
- Size: 82 X 55 X 180mm
- Display: 122 X 32 dots LCD, 2 LED

Design and specifications are subject to change without prior notice